

# MINIRAE® 3000 +

Portable Handheld VOC Monitor

The MiniRAE 3000 + is a comprehensive handheld VOC (Volatile Organic Compound) monitor that uses a third-generation patented PID technology to accurately measure one of the highest levels of ionizable chemicals available on the market.

It provides full-range measurement from 0 to 15,000 ppm of VOCs. The MiniRAE 3000 + has a built-in wireless modem that allows realtime data connectivity with the command center located up to 2 miles (3 km) away through a Bluetooth connection to a RAELink 3\* portable modem or optionally via Mesh Network.



- Highly accurate VOC measurements
- Reflex PID Technology™
- Low maintenance — easy access to lamp and sensor
- Low cost of ownership
- 3-year 10.6eV lamp warranty
- BLE module & dedicated APP for Enhanced Datalogging capability

*Workers can quickly measure VOCs and wirelessly transmit data*

## APPLICATIONS

- Oil and Gas
- HazMat
- Industrial Safety
- Civil Defense
- Environmental and Indoor Air Quality

## FEATURES AND BENEFITS



Third-generation patented PID technology



Reflex PID Technology™



VOC detection range from 0 to 15,000 ppm



3-second response time



Humidity compensation with built-in humidity and temperature sensors



Six-month datalogging



Highly connectivity capability through multiple wireless module options



Large graphic display with integrated flashlight



Multi-language support with 10 languages encoded



IP-67 waterproof design

**Honeywell**

# Minirae® 3000+ Technical Specifications

INSTRUMENT SPECIFICATIONS	
Size	10" L x 3.0" W x 2.5" H (25.5 cm x 7.6 cm x 6.4 cm)
Weight	26 oz (738 g)
Sensors	Photoionization sensor with standard 10.6 eV or optional 9.8 eV or 11.7 eV lamp
Battery	<ul style="list-style-type: none"> <li>Rechargeable, external field-replaceable Lithium-Ion battery pack</li> <li>Alkaline battery adapter</li> </ul>
Running time	16 hours of operation (12 hours with alkaline battery adapter)
Display Graphic	4 lines, 28 x 43 mm, with LED backlight for enhanced display readability
Keypad	1 operation and 2 programming keys, 1 flashlight on/off
Direct Readout	Instantaneous reading <ul style="list-style-type: none"> <li>VOCs as ppm by volume (mg/m<sup>3</sup>)</li> <li>High values</li> <li>STEL and TWA</li> <li>Battery and shutdown voltage</li> <li>Date, time, temperature</li> </ul>
Alarms	95dB at 12" (30 cm) buzzer and flashing red LED to indicate exceeded preset limits <ul style="list-style-type: none"> <li>High: 3 beeps and flashes per second</li> <li>Low: 2 beeps and flashes per second</li> <li>STEL and TWA: 1 beep and flash per second</li> <li>Alarms latching with manual override or automatic reset</li> <li>Additional diagnostic alarm and display message for low battery and pump stall</li> </ul>
EMC/RFI	Compliant with EMC directive (2004/108/EC) EMI and ESD test: 100MHz to 1GHz 30V/m, no alarm Contact: ±4kV Air: ±8kV, no alarm
IP Rating	<ul style="list-style-type: none"> <li>IP-67 unit off and without flexible probe</li> <li>IP-65 unit running</li> </ul>
Datalogging	Standard 6 months at one-minute intervals
Calibration	Two-point or three-point calibration for zero and span. Reflex PID Technology™ Calibration memory for 8 calibration gases, alarm limits, span values and calibration dates
Sampling Pump	<ul style="list-style-type: none"> <li>Internal, integrated flow rate at 500 cc/mn</li> <li>Sample from 100' (30m) horizontally or vertically</li> </ul>
Low Flow Alarm	Auto pump shutoff at low-flow condition
Communication & Data Download	<ul style="list-style-type: none"> <li>Download data and upload instrument set-up from PC through charging cradle or using BLE module and dedicated APP</li> <li>Wireless data transmission through built-in RF modem</li> </ul>
Wireless Network	Mesh RAE Systems Dedicated Wireless Network
Wireless Range (Typical)	Up to 15ft (5m) for BLE EchoView Host: LOS > 660 ft (200 m) ProRAE Guardian & RAEMesh Reader: LOS > 660 ft (200 m) ProRAE Guardian & RAELink3 Mesh: LOS > 330 ft (100 m)
Safety Certifications	<b>US and Canada:</b> CSA, Classified as Intrinsically Safe for use in Class I, Division 1, Groups A, B, C, D <b>Europe:</b> ATEX II 2G EEx ia IIC T4
Temperature	-4° to 122° F (-20° to 50° C)
Humidity	0% to 95% relative humidity (non-condensing)
Attachments	Durable bright yellow rubber boot
Warranty	3 years for 10.6 eV lamp, 1 year for pump, battery, sensor and instrument
Wireless Frequency	ISM license-free band. IEEE 802.15.4 Sub 1GHz
Wireless Approvals	FCC Part 15, CE R&TTE, Others <sup>1</sup>
Radio Module	Supports BLE or Bluetooth or RM900

SENSOR SPECIFICATIONS			
Gas Monitor	Range	Resolution	Response Time T90
VOCs	0 to 999.9 ppm 1,000 to 15,000 ppm	0.1 ppm 1 ppm	< 3 s < 3 s

## MONITOR ONLY INCLUDES:

- MiniRAE 3000+ Monitor, Model PGM-7320
- Wireless communication module built in, as specified
- Datalogging with ProRAE Studio II Package
- Charging/download adapter
- RAE UV lamp, as specified
- Flex-I-Probe™
- External filter
- Rubber boot
- Alkaline battery adapter
- Lamp-cleaning kit
- Tool kit
- Soft leather case

## OPTIONAL CALIBRATION KIT ADDS:

- 100 ppm isobutylene calibration gas, 34L
- Calibration regulator and flow controller

## OPTIONAL GUARANTEED COST-OF-OWNERSHIP PROGRAM:

- 4-year repair and replacement warranty
- Annual maintenance service

<sup>1</sup> Contact RAE Systems for country-specific wireless approvals and certificates. Specifications are subject to change.

Note: Due to ongoing research and product improvement, specifications are subject to change without notice.

DS\_Honeywell BW RigRat\_DS052419-00\_US-EN | 03/20  
© 2020 Honeywell International Inc.

For More Information  
safety.honeywell.com

THE  
FUTURE  
IS  
WHAT  
WE  
MAKE IT

**Honeywell**

Authorized Distributor the only one in Thailand for  
Spare Parts, After Sales, and ISO 17025 Calibration  
Laboratory Standard

\\ @ # 0 .  
u o M " "